

A50

SLENDER

Smart MiniPOS+



Food & Beverage



Fashion & Retail



Transportation



SMARTPOS



Powered by
Android 8.1



PCI 5
SRED



4.5" HD
Display



Up to 5MP Rear
0.3MP Front






















Advanced
Connectivity

A50

Android MiniPOS+

SPECIFICATIONS

	Operating System	Paydroid Powered by Android 8.1
	Processor	Cortex A53 + ARM
	Memory	8GB eMMC Flash + 1GB DDR RAM Optional: 16GB eMMC Flash + 2GB DDR RAM Extended Micro SD card slot up to 128GB
	Card Readers	Chip & PIN NFC Contactless
	Cameras	2MP Rear-Facing Optional: Rear-Facing 5MP 0.3MP Front-Facing
	Displays	4.5" IPS WXGA 720 x 1280 Pixels Multi-Point Capacitive HD Touch Screen
	Comms Configurations	4G + WiFi (2.4GHz)+ Bluetooth 4.0
	Battery	2500mAh 3.8V
	Printer	No
	SIM / SAM	1 x SIM + 1 x Micro SD Optional: 2 x SIM
	Positioning	GPS
	Keys / Buttons	4 Keys: Power ON/OFF Volume+ Volume- Scan button
	Audio	1 Buzzer 1 Speaker 1 Microphone
	Ports	1 Type C USB OTG 1 Audio Jack & 1 Receiver 5 PIN POGO PIN
	Adapter	Input: 100 - 240V AC, 50Hz / 60Hz Output: 5.0V DC, 2.0A
	Physical	138 * 69.5 * 12 mm 163g (Including Battery)
	Environmental	-10°C ~ 50°C (14°F ~ 122°F) Operating Temperature -20°C ~ 70°C (-4°F ~ 158°F) Storage Temperature 5% ~ 96% Relative Humidity, Non-Condensing
	Accessories	B50: Charging Base 1 Power Port (Type C) 98 * 62 * 49 mm B51: 5-Devices Charging Base 98 * 210 * 49 mm
	Certifications	PCI PTS 5.x SRED EMV L1 & L2 EMV Contactless L1 Visa payWave MasterCard Contactless UPI qUICS Amex ExpressPay Discover D-PAS JCB J/Speedy Interac Flash MasterCard TQM CE RoHs FCC

